

# RODAJAS DE PVC NARANJAS



## CARACTERÍSTICAS

- **RUEDA** de PVC.
- **RIN** de polipropileno.
- **SOPORTE** tipo placa.



\*Doble balero incluido.

## FIJAS

CÓDIGO										
	pulg	mm	kg	lb	mm	mm	mm	mm		
<b>SIN FRENO</b>										
RV5F	2"	50.8	60	132.3	25	74	70 x 52	52 x 35	8 x 11	1
RV6F	2-1/2"	63.5	70	154.35	31	94	95 x 65	75 x 47	8 x 11	1
RV7F	3"	76.2	80	176.4	31	107	95 x 65	75 x 47	8 x 11	1
RV10F	4"	101.6	90	198.45	31	130	95 x 65	75 x 47	8 x 11	1

## GIRATORIAS

CÓDIGO										
	pulg	mm	kg	lb	mm	mm	mm	mm		
<b>GIRATORIAS SIN FRENO</b>										
RV5G	2"	50.8	60	132.3	25	74	70 x 52	52 x 35	8 x 11	1
RV6G	2-1/2"	63.5	70	154.35	31	94	92 x 62	75 x 47	8 x 11	1
RV7G	3"	76.2	80	176.4	31	107	92 x 62	75 x 47	8 x 11	1
RV10G	4"	101.6	90	198.45	31	130	92 x 62	75 x 47	8 x 11	1
<b>GIRATORIAS CON FRENO</b>										
RV5B	2"	50.8	60	132.3	25	74	70 x 52	52 x 35	8 x 11	1
RV6B	2-1/2"	63.5	70	154.35	31	94	92 x 62	75 x 47	8 x 11	1
RV7B	3"	76.2	80	176.4	31	107	92 x 62	75 x 47	8 x 11	1
RV10B	4"	101.6	90	198.45	31	130	92 x 62	75 x 47	8 x 11	1

\*Doble balero incluido.

## CARACTERÍSTICAS

- **TEMPERATURA** operación: -20° C a 70° C.
- **VELOCIDAD** máxima de operación: 3 km/h.

## USOS

- **IDEAL PARA** vehículos de manejo de carga, carros móviles o mobiliario con mucho peso.